

## 200Z (UL LISTED TO CANADIAN SAFETY STANDARDS)

### FEATURES

- ♦ best selling low profile industrial strobe light
- ♦ powder coated, die cast aluminum case
- ♦ fully encapsulated circuitry
- ♦ aluminum clamp ring

### BENEFITS

- ♦ easy field servicing
- ♦ available in single flash only, 65 ± 5 fpm
- ♦ weather and corrosion resistant

### APPLICATIONS

- ♦ suitable for fire alarm systems, assembly line malfunctions, automatic door systems, alarm systems and calling stations eg. nursing stations
- ♦ surface mount and 1/2" NPT conduit mount
- ♦ rated for -30°C to +70°C



### MODELS

200ZUL-12Colour	(12Vdc, single flash, specify colour)
200ZUL-24Colour	(24Vdc, single flash, specify colour)
200ZUL-36Colour	(36Vdc, single flash, specify colour)
200ZUL-120Colour	(120VAC, single flash, specify colour)
200ZUL-240Colour	(240VAC, single flash, specify colour)

### SPECIFICATIONS

Voltages	Amps	Joules	Approvals
12Vdc	0.5	3	UL Listed to Canadian Safety Standards, NEMA 4X
24Vdc	0.3	3	UL Listed to Canadian Safety Standards, NEMA 4X
36Vdc	0.2	3	UL Listed to Canadian Safety Standards, NEMA 4X
120VAC	0.1	3	UL Listed to Canadian Safety Standards, NEMA 4X
240VAC	0.1	3	UL Listed to Canadian Safety Standards, NEMA 4X

### MEASUREMENTS

Height .....4"  
Width .....4 1/8"

### REPLACEMENT PARTS

Polycarbonate Lens .....330  
Strobe tube .....129-Z  
Power Supply .....181 -Z-Specify  
(available in 12, 24, or 36Vdc and 120 or 240VAC)  
Clamp Ring .....374-Z

### LENS COLOURS

Amber   
Red   
Clear 