

## 201Z (UL LISTED TO CANADIAN SAFETY STANDARDS)

### FEATURES

- ♦ low profile, lightweight, completely polycarbonate industrial strobe light
- ♦ polycarbonate base with snap in lens
- ♦ fully encapsulated circuitry

### BENEFITS

- ♦ easy field servicing
- ♦ available in 12, 24, or 36Vdc (must specify) and 120 or 240VAC (must specify)
- ♦ single flash only, 65 ± 5 fpm
- ♦ weather and corrosion resistant

### APPLICATIONS

- ♦ suitable for underground vehicles eg. mine shaft cars, tow motors, low profile applications, indoor and outdoor applications, alarm systems, calling stations and portable battery applications
- ♦ surface mount and 1/2" NPT conduit mount
- ♦ rated for -30°C to +70°C



### MODELS

201ZUL-12Colour	(12Vdc, single flash, specify colour)
201ZUL-24Colour	(24Vdc, single flash, specify colour)
201ZUL-36Colour	(36Vdc, single flash, specify colour)
201ZUL-120Colour	(120VAC, single flash, specify colour)
201ZUL-240Colour	(240VAC, single flash, specify colour)

### SPECIFICATIONS

Voltages	Amps	Joules	Approvals
12Vdc	0.5	3	UL Listed to Canadian Safety Standards, NEMA 4X
24Vdc	0.3	3	UL Listed to Canadian Safety Standards, NEMA 4X
36Vdc	0.2	3	UL Listed to Canadian Safety Standards, NEMA 4X
120VAC	0.1	3	UL Listed to Canadian Safety Standards, NEMA 4X
240VAC	0.1	3	UL Listed to Canadian Safety Standards, NEMA 4X



### MEASUREMENTS

Height .....4 1/4"  
Width .....4 1/4"

### REPLACEMENT PARTS

Polycarbonate Lens .....330  
Strobe tube .....129-Z  
Power Supply .....181-Z-Specify  
(available in 12, 24 or 36Vdc and 120 or 240VAC)  
O-Ring Gasket .....381

### LENS COLOURS

 Amber  
 Red  
 Clear