

I200D

FEATURES

- ♦ ideal portable industrial warning light wherever 110VAC is available
- ♦ 5' electrical cord with U ground plug
- ♦ anodized aluminum case
- ♦ fully encapsulated circuitry

BENEFITS

- ♦ easy field servicing
- ♦ weather and corrosion resistant
- ♦ single flash (standard) or double flash (order model I200DD)

APPLICATIONS

- ♦ suitable for temporary hazard areas where portability is necessary
- ♦ construction areas
- ♦ portable placement and magnetic mount (model I200DM)
- ♦ rated for -30°C to +70°C



MEASUREMENTS

Height7 1/4"
Width7 5/8"

REPLACEMENT PARTS

Polycarbonate Lens300
Strobe tube129
Power Supply181-120V
Head Assembly180
(single flash head)
Head Assembly180D
(double flash head)
Base Rubber111
Bottom Plate104-S
(specify for 200D)
magnet and Nut177

MODELS

I200D-120V-Colour (120VAC, single flash, specify colour)
I200DD-120V-Colour (120VAC, double flash, specify colour)

SPECIFICATIONS

Voltages	Amps	Joules	Approvals
120VAC	0.1	10-14 \square	CSA

\square depending on flash pattern chosen (single or double)

LENS COLOURS

 Amber
 Red
 Clear