




**MEASUREMENTS**

Height .....7 3/16"  
 Width .....8 1/16"

**REPLACEMENT PARTS**

Polycarbonate Lens .....300  
 Strobe tube .....129  
 Power Supply .....181-12V  
 Power Supply .....181-72V  
 Power Supply .....181-120V  
 Power Supply .....181-240V  
 Head Assembly .....180  
 (single flash head)  
 Head Assembly .....180D  
 (double flash head)

**LENS COLOURS**

Amber   
 Red   
 Clear 

**I200EC**

**FEATURES**

- ♦ heavy duty industrial strobe light
- ♦ powder coated cast case

**BENEFITS**

- ♦ extremely durable and heavy duty
- ♦ fully encapsulated circuitry
- ♦ single or double flash
- ♦ fused for reverse polarity protection

**APPLICATIONS**

- ♦ suitable for heavy duty industrial and commercial, indoor or outdoor applications such as overhead cranes, repair vehicles and institutional locations
- ♦ surface mount, 3/4" NPT conduit mount or cast base may be used as a junction box
- ♦ rated for -30°C to +70°C



*Note:  
 surge suppression available for  
 certain applications*

**MODELS**

I200EC-12V-Colour	(12-48Vdc, single flash, specify colour)
I200ECD-12-Colour	(12-48Vdc, double flash, specify colour)
I200EC-72V-Colour	(72-125Vdc, single flash, specify colour)
I200ECD-72-Colour	(72-125Vdc, double flash, specify colour)
I200EC-120-Colour	(120VAC, single flash, specify colour)
I200ECD-120-Colour	(120VAC, double flash, specify colour)
I200EC-240-Colour	(240VAC, single flash, specify colour)
I200ECD-240Colour	(240VAC, double flash, specify colour)
I200EC-200-Colour	(200/300 AC/DC, single flash, specify colour)

**SPECIFICATIONS**

Voltages	Amps	Joules	Approvals
12-48Vdc	2.5	10-14 α	CSA
72-125Vdc	0.5	10-14 α	CSA
120VAC	0.1	10-14 α	CSA
240VAC	0.1	10-14 α	CSA

α depending on flash pattern chosen (single or double)