

MEASUREMENTS

Height10"
 Width5 1/2"

REPLACEMENT PARTS

Polycarbonate Lens300-S
 Strobe tube129
 Power Supply181-S-120V
 (single flash)
 Power Supply181-SD-120V
 (double flash)
 Clamp Ring365
 Hanger HookHOOK
 (with safety screw)

I200SCH

FEATURES

- ♦ strobe warning light with hook for total portability
- ♦ powder coated die-cast aluminum case
- ♦ available in single and double flash
- ♦ 5' electrical cord with U ground plug
- ♦ fully encapsulated circuitry
- ♦ stainless steel clamp ring

BENEFITS

- ♦ easy field servicing
- ♦ weather and corrosion resistant
- ♦ electronic components and housing, CSA approved

APPLICATIONS

- ♦ suitable for a variety of industrial applications where portability is essential
- ♦ hook mount
- ♦ rated for -30°C to +70°C



MODELS

I200SCH-Colour (120VAC, single flash, specify colour)
 I200SCHD-Colour (120VAC, double flash, specify colour)

LENS COLOURS

Amber
 Red
 Clear

SPECIFICATIONS

Voltages	Amps	Joules	Approvals
120VAC	0.1	10-14 ♂	CSA

♂ depending on flash pattern chosen (single or double)