

**MEASUREMENTS**

Height .....7 1/2"  
 Width .....8 3/8"

**REPLACEMENT PARTS**

Polycarbonate Outer Dome .134-2  
 Polycarbonate Inner Lens . .300  
 Strobe tube .....129  
 Power Supply .....181-12V  
 Power Supply .....181-72V  
 Power Supply .....181-120V  
 Power Supply .....181-240V  
 Head Assembly .....180  
 (single flash head)  
 Head Assembly .....180D  
 (double flash head)  
 Stainless Steel Clamp Ring . .4022

**I201B**

**FEATURES**

- ♦ dependable and rugged
- ♦ anodized aluminum base
- ♦ enclosed bottom
- ♦ fully encapsulated circuitry
- ♦ stainless steel clamp ring



**BENEFITS**

- ♦ easy field servicing
- ♦ single or double flash
- ♦ fused for reverse polarity protection
- ♦ weather and corrosion resistant
- ♦ outer dome keeps inner lens dirt free and cleans easily

*Note:  
 surge suppression available for  
 certain applications*

**APPLICATIONS**

- ♦ suitable for heavy duty industrial and commercial applications including high dust locations, security applications, and locomotives
- ♦ surface mount and 3/4" NPT conduit mount , aluminum base can be used as a junction box
- ♦ rated for -30°C to +70°C

*For double flash, order part I201BD*

**MODELS**

I201B-12V-Colour	(12-48Vdc, single flash, specify colour)
I201BD-12V-Colour	(12-48Vdc, double flash, specify colour)
I201B-72V-Colour	(72-125Vdc, single flash, specify colour)
I201BD-72V-Colour	(72-125Vdc, double flash, specify colour)
I201B-120V-Colour	(120VAC, single flash, specify colour)
I201BD-120-Colour	(120VAC, double flash, specify colour)
I201B-240V-Colour	(240VAC, single flash, specify colour)
I201BD-240-Colour	(240VAC, double flash, specify colour)

**SPECIFICATIONS**

Voltages	Amps	Joules	Approvals
12-48Vdc	2.5	10-14 α	CSA
72-125Vdc	0.5	10-14 α	CSA
120VAC	0.1	10-14 α	CSA
240VAC	0.1	10-14 α	CSA

α depending on flash pattern chosen (single or double)

**LENS COLOURS**

