

MEASUREMENTS

Height4 1/4"
 Width4 1/4"

REPLACEMENT PARTS

Polycarbonate Lens330
 Strobe tube129-Z
 Power Supply181-Z-Specify
(available in 12, 24 or 36Vdc and 120 or 240VAC)
 O-Ring Gasket381

I201Z

FEATURES

- ♦ low profile, lightweight, completely polycarbonate industrial strobe light
- ♦ polycarbonate base with snap in lens
- ♦ fully encapsulated circuitry



BENEFITS

- ♦ easy field servicing
- ♦ available in 12 or 24Vdc, (must specify) and 24, 120 or 240VAC (must specify)
- ♦ single flash only, 65 ± 5 fpm
- ♦ weather and corrosion resistant

APPLICATIONS

- ♦ suitable for underground vehicles eg. mine shaft cars, tow motors, low profile applications, indoor and outdoor applications, alarm systems, calling stations and portable battery applications
- ♦ surface mount and 1/2" NPT conduit mount
- ♦ rated for -30°C to +70°C

MODELS

I201Z-12V-Colour	(12Vdc, single flash, specify colour)
I201Z-24V-Colour	(24Vdc, single flash, specify colour)
I201Z-120V-Colour	(120VAC, single flash, specify colour)
I201Z-240V-Colour	(240VAC, single flash, specify colour)

SPECIFICATIONS

Voltages	Amps	Joules	Approvals
12Vdc	0.5	3	CSA, NEMA 4X
24Vdc	0.3	3	CSA, NEMA 4X
120VAC	0.1	3	CSA, NEMA 4X
240VAC	0.1	3	CSA, NEMA 4X

LENS COLOURS

-  Amber
-  Red
-  Clear