

## I20FIS & FIS-1

### FEATURES

- ♦ economical and compact low profile stedi burn incandescent light
- ♦ powder coated, die cast aluminum case
- ♦ stainless steel clamp ring

### BENEFITS

- ♦ easy field servicing
- ♦ fully encapsulated circuitry
- ♦ stedi burn
- ♦ weather and corrosion resistant

### APPLICATIONS

- ♦ suitable for tow motors, smaller service vehicles, various indoor factory vehicles, nursing stations, loading doors and assembly lines



Model I20FI-1

Model I20FI

### APPLICATIONS CONT'D

- ♦ surface mount, 1/2" NPT conduit mount or two knockout holes to accommodate octagon box
- ♦ rated for -30°C to +70°C

### MODELS

I20FIS-12V-Colour	(12Vdc, stedi burn, specify colour)
I20FIS-24V-Colour	(24Vdc, stedi burn, specify colour)
I20FIS-36V-Colour	(36Vdc, stedi burn, specify colour)
I20FIS-48V-Colour	(48Vdc, stedi burn, specify colour)
I20FIS-24VAColour	(24VAC, stedi burn, specify colour)
I20FIS-120-Colour	(120VAC, stedi burn, specify colour)
I20FIS-240-Colour	(240VAC, stedi burn, specify colour)
I20FIS-1-12Colour	(12Vdc, stedi burn, specify colour)
I20FIS-1-24Colour	(24Vdc, stedi burn, specify colour)
I20FIS-1-36Colour	(36Vdc, stedi burn, specify colour)
I20FIS-1-48Colour	(48Vdc, stedi burn, specify colour)
I20FIS-124AColour	(24VAC, stedi burn, specify colour)
I20FIS-1120Colour	(120VAC, stedi burn, specify colour)
I20FIS-1240Colour	(240VAC, stedi burn, specify colour)

### SPECIFICATIONS

Voltages	Amps	Watts	Approvals
12Vdc	1.0	12	CSA
24Vdc	1.0	24	CSA
36Vdc	1.0	36	CSA
48Vdc	0.5	24	CSA
24VAC	0.25	24	CSA
120VAC	0.1	40	CSA
240VAC	0.1	25	CSA

### MEASUREMENTS

Height .....7 1/8"  
Width .....6"

### REPLACEMENT PARTS

Polycarbonate Outer Dome	.325
Polycarbonate Inner Lens	...333
Bulb 12V	.....2073-94
Bulb 24V	.....2073-1638
Bulb 36V	.....2073-1062
Bulb 48V	.....2073-10498
Bulb 120VAC	.....2073-40T8DC
Bulb 240VAC	.....2073-25T8DC
Power Supply	.....181-FI-12V (multi-voltage 12-48Vdc)
Power Supply	.....181-FI-120V
Power Supply	.....181-FI-240V
Stainless Clamp Ring	.....4122

### LENS COLOURS

-  Amber
-  Red
-  Clear