

## I20ZI & I201ZI

### FEATURES

- ♦ economical and compact low profile flashing incandescent lights
- ♦ powder coated, die cast aluminum base with aluminum clamp ring (model I-20ZI)
- ♦ completely polycarbonate base and snap in lens (model I-201ZI)



Model I20ZI

Model I201ZI

### BENEFITS

- ♦ easy field servicing
- ♦ fully encapsulated circuitry
- ♦ available in single flash or stedi burn
- ♦ weather and corrosion resistant

### APPLICATIONS

- ♦ suitable for smaller service vehicles, various indoor factory vehicles, or dangerous area warning applications
- ♦ surface mount and 1/2" NPT conduit mount
- ♦ rated for -30°C to +70°C

### MEASUREMENTS

#### Model I-20ZI

Height .....4"  
Width .....4 1/8"

#### Model I-201ZI

Height .....4 1/4"  
Width .....4 1/4"

### REPLACEMENT PARTS

Polycarbonate Lens .....330  
Bulb 12V .....2073-94  
Bulb 24V .....2073-1638  
Bulb 36V .....2073-1062  
Bulb 48V .....2073-10498  
Bulb 120VAC .....2073-40T8DC  
Bulb 240VAC .....2073-25T8DC  
Power Supply .....181-FI-12V  
(multi-voltage 12-48Vdc)  
Power Supply .....181-FI-120V  
Power Supply .....181-FI-240V  
Clamp Ring .....374-Z  
O-Ring Gasket (model I-201ZI) .381

### MODELS (I20ZI)

I20ZI-12V-Colour	(12Vdc, single flash, specify colour)
I20ZI-24V-Colour	(24Vdc, single flash, specify colour)
I20ZI-36V-Colour	(36Vdc, single flash, specify colour)
I20ZI-48V-Colour	(48Vdc, single flash, specify colour)
I20ZI-24VACColour	(24VAC, single flash, specify colour)
I20ZI-120V-Colour	(120VAC, single flash, specify colour)
I20ZIS-12V-Colour	(12Vdc, stedi burn, specify colour)
I20ZIS-24V-Colour	(24Vdc, stedi burn, specify colour)
I20ZIS-36V-Colour	(36Vdc, stedi burn, specify colour)
I20ZIS-48V-Colour	(48Vdc, stedi burn, specify colour)
I20ZIS-24VACColour	(24VAC, stedi burn, specify colour)
I20ZIS-120Colour	(120VAC, stedi burn, specify colour)

### MODELS (I201ZI)

I201ZI-12V-Colour	(12Vdc, single flash, specify colour)
I201ZI-24V-Colour	(24Vdc, single flash, specify colour)
I201ZI-36V-Colour	(36Vdc, single flash, specify colour)
I201ZI-48V-Colour	(48Vdc, single flash, specify colour)
I201ZI-24VACColour	(24VAC, single flash, specify colour)
I201ZI-120-Colour	(120VAC, single flash, specify colour)
I201ZIS-12-Colour	(12Vdc, stedi burn, specify colour)
I201ZIS-24-Colour	(24Vdc, stedi burn, specify colour)
I201ZIS-36-Colour	(36Vdc, stedi burn, specify colour)
I201ZIS-48-Colour	(48Vdc, stedi burn, specify colour)
I201ZIS-24AColour	(24VAC, stedi burn, specify colour)
I201ZIS-120Colour	(120VAC, stedi burn, specify colour)

### SPECIFICATIONS

Voltages	Amps	Watts	Approvals
12Vdc	1.0	12	CSA
24Vdc	1.0	24	CSA
36Vdc	1.0	36	CSA
48Vdc	0.5	24	CSA
24VAC	1.0	24	CSA
120VAC	0.1	40	CSA
240VAC	0.1	25	CSA

### LENS COLOURS

-  Amber
-  Red
-  Clear